

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier: MORAVIA - VENTOSHORT SK10-9002

### **1.2** Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Paint. For professional user/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

### **1.3** Details of the supplier of the safety data sheet:

MORAVİA BOYA VE KİMYA SAN.TİC.LTD.ŞTİ FEVZİ ÇAKMAK CADDESİ NO:2 SEFAKÖY/ KÜÇÜKÇEKMECE İSTANBUL - TURKEY Phone.: +90 212 579 13 36 - Fax: +90 212 426 55 12 moravia@moravia.com.tr www.moravia.com.tr

### 1.4 Emergency telephone number:

### SECTION 2: HAZARDS IDENTIFICATION \*\*

### 2.1 Classification of the substance or mixture:

## CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Asp. Tox. 1: Aspiration hazard, Category 1, H304 Flam. Liq. 2: Flammable liquids, Category 2, H225 Repr. 2: Reproductive toxicity, Category 2, H361d Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1A: Sensitisation, skin, Category 1A, H317 STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

### 2.2 Label elements:

#### CLP Regulation (EC) No 1272/2008:

Danger



#### Hazard statements:

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways Flam. Liq. 2: H225 - Highly flammable liquid and vapour Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation Skin Sens. 1A: H317 - May cause an allergic skin reaction STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure STOT SE 3: H336 - May cause drowsiness or dizziness

### **Precautionary statements:**

P201: Obtain special instructions before use

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of water

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P308+P313: IF exposed or concerned: Get medical advice/attention

P370+P378: In case of fire: Use ABC powder extinguisher to extinguish

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

### Supplementary information:

Contains 2-butanone oxime

### Substances that contribute to the classification

\*\* Changes with regards to the previous version



## SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)

Toluene; Hydrocarbons, C9-unsaturated, polymerised; Cobalt bis(2-ethylhexanoate)

### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

\*\* Changes with regards to the previous version

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

Chemical description: Miscellaneous products

#### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

|  | Identification   |  | Chemical name/Classification   |                             | Concentration |  |
|--|--|--|--|-----------------------------|---------------|--|
| CAS:   | 108-88-3   | Toluene <sup>(1)</sup>                   |  | ATP CLP00                   |               |  |
| REACH:   | 203-625-9<br>601-021-00-3<br>01-2119471310-51-<br>XXXX   | Regulation 1272/2008                     | Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT<br>RE 2: H373; STOT SE 3: H336 - Danger | () () ()                    | 25 - <50 %    |  |
| CAS:   | 1330-20-7  | Xylene <sup>(1)</sup>                    |  | ATP CLP00                   |               |  |
| REACH:   | 215-535-7<br>601-022-00-9<br>01-2119488216-32-<br>XXXX   | Regulation 1272/2008                     | Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning   | (1) (1)                     | 2,5 - <10 %   |  |
| CAS:   | 71302-83-5   | Hydrocarbons, C9-ur                      | saturated, polymerised <sup>(1)</sup>  | Self-classified             |               |  |
| REACH:   | 615-276-3<br>Non-applicable<br>01-2119555292-40-<br>XXXX | Regulation 1272/2008                     | Aquatic Chronic 3: H412; Skin Sens. 1A: H317 - Warning   |                             | 2,5 - <10 %   |  |
| CAS:   | 108-65-6   | 2-methoxy-1-methyl                       | ethyl acetate <sup>(2)</sup>   | ATP ATP01                   |               |  |
|  | 203-603-9<br>607-195-00-7<br>01-2119475791-29-<br>XXXX   | Regulation 1272/2008                     | Flam. Liq. 3: H226 - Warning   | <b>(</b>                    | 2,5 - <10 %   |  |
| CAS:   | 136-52-7   | Cobalt bis(2-ethylhe                     | kanoate) <sup>(1)</sup>  | Self-classified             |               |  |
| EC: 205-250-6<br>Index: Non-applicable<br>REACH: 01-2119524678-29-<br>XXXX |  | Regulation 1272/2008                     | Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Repr. 1B:<br>H360; Skin Sens. 1A: H317 - Danger      | (1) <b>(b)</b> ( <b>b</b> ) | <1 %          |  |
| CAS: 96-29-7   |  | 2-butanone oxime <sup>(1)</sup> ATP CLPO |  |                             |               |  |
| REACH:   | 202-496-6<br>616-014-00-0<br>01-2119539477-28-<br>XXXX   | Regulation 1272/2008                     | Acute Tox. 4: H312; Carc. 2: H351; Eye Dam. 1: H318; Skin Sens. 1: H317 -<br>Danger                                      | 1 2 3                       | <1 %          |  |
| CAS:   | 22464-99-9   |  |  |                             |               |  |
| EC: 245-018-1<br>Index: Non-applicable<br>REACH: 01-2119979088-21-<br>XXXX |  | Regulation 1272/2008                     | Repr. 2: H361d - Warning   | <b></b>                     | <1 %          |  |

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

<sup>(2)</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

## SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. **By inhalation:** 

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.



## SECTION 4: FIRST AID MEASURES (continued)

## By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

### By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

## 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

## 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

### 6.3 Methods and material for containment and cleaning up:

#### It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.



## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

## 7.2 Conditions for safe storage, including any incompatibilities:

| Α | Technical measures for st  | orage    |
|---|----------------------------|----------|
|   | Minimum Temp.:             | 5 °C     |
|   | Maximum Temp.:             | 30 °C    |
|   | Maximum time:              | 6 Months |
| р | Concept conditions for sta |          |

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

| Identification                  | Oc           | Occupational exposure limits |                       |  |  |
|---------------------------------|--------------|------------------------------|-----------------------|--|--|
| Toluene                         | IOELV (8h)   | 50 ppm                       | 192 mg/m <sup>3</sup> |  |  |
| CAS: 108-88-3 EC: 203-625-9     | IOELV (STEL) | 100 ppm                      | 384 mg/m <sup>3</sup> |  |  |
| Xylene                          | IOELV (8h)   | 50 ppm                       | 221 mg/m <sup>3</sup> |  |  |
| CAS: 1330-20-7 EC: 215-535-7    | IOELV (STEL) | 100 ppm                      | 442 mg/m <sup>3</sup> |  |  |
| 2-methoxy-1-methylethyl acetate | IOELV (8h)   | 50 ppm                       | 275 mg/m <sup>3</sup> |  |  |
| CAS: 108-65-6 EC: 203-603-9     | IOELV (STEL) | 100 ppm                      | 550 mg/m <sup>3</sup> |  |  |

#### DNEL (Workers):

|                |            | Short e               | xposure               | Long e                | xposure               |
|----------------|------------|-----------------------|-----------------------|-----------------------|-----------------------|
| Identification |            | Systemic              | Local                 | Systemic              | Local                 |
| Toluene        | Oral       | Non-applicable        | Non-applicable        | Non-applicable        | Non-applicable        |
| CAS: 108-88-3  | Dermal     | Non-applicable        | Non-applicable        | 384 mg/kg             | Non-applicable        |
| EC: 203-625-9  | Inhalation | 384 mg/m <sup>3</sup> | 384 mg/m <sup>3</sup> | 192 mg/m <sup>3</sup> | 192 mg/m <sup>3</sup> |
| Xylene         | Oral       | Non-applicable        | Non-applicable        | Non-applicable        | Non-applicable        |
| CAS: 1330-20-7 | Dermal     | Non-applicable        | Non-applicable        | 180 mg/kg             | Non-applicable        |
| EC: 215-535-7  | Inhalation | 289 mg/m <sup>3</sup> | 289 mg/m <sup>3</sup> | 77 mg/m <sup>3</sup>  | Non-applicable        |



# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

|                                      |            | Short          | exposure       | Long                  | exposure                 |
|--------------------------------------|------------|----------------|----------------|-----------------------|--------------------------|
| Identification                       |            | Systemic       | Local          | Systemic              | Local                    |
| 2-methoxy-1-methylethyl acetate      | Oral       | Non-applicable | Non-applicable | Non-applicable        | Non-applicable           |
| CAS: 108-65-6                        | Dermal     | Non-applicable | Non-applicable | 153,5 mg/kg           | Non-applicable           |
| EC: 203-603-9                        | Inhalation | Non-applicable | Non-applicable | 275 mg/m <sup>3</sup> | Non-applicable           |
| Cobalt bis(2-ethylhexanoate)         | Oral       | Non-applicable | Non-applicable | Non-applicable        | Non-applicable           |
| CAS: 136-52-7                        | Dermal     | Non-applicable | Non-applicable | Non-applicable        | Non-applicable           |
| EC: 205-250-6                        | Inhalation | Non-applicable | Non-applicable | Non-applicable        | 0,2351 mg/m <sup>3</sup> |
| 2-butanone oxime                     | Oral       | Non-applicable | Non-applicable | Non-applicable        | Non-applicable           |
| CAS: 96-29-7                         | Dermal     | 2,5 mg/kg      | Non-applicable | 1,3 mg/kg             | Non-applicable           |
| EC: 202-496-6                        | Inhalation | Non-applicable | Non-applicable | 9 mg/m <sup>3</sup>   | 3,33 mg/m <sup>3</sup>   |
| 2-ethylhexanoic acid, zirconium salt | Oral       | Non-applicable | Non-applicable | Non-applicable        | Non-applicable           |
| CAS: 22464-99-9                      | Dermal     | Non-applicable | Non-applicable | 15,75 mg/kg           | Non-applicable           |
| EC: 245-018-1                        | Inhalation | Non-applicable | Non-applicable | 5 mg/m <sup>3</sup>   | Non-applicable           |

## DNEL (General population):

|                                      |            | Short exposure        |                       | Long exposure          |                         |
|--------------------------------------|------------|-----------------------|-----------------------|------------------------|-------------------------|
| Identification                       |            | Systemic              | Local                 | Systemic               | Local                   |
| Toluene                              | Oral       | Non-applicable        | Non-applicable        | 8,13 mg/kg             | Non-applicable          |
| CAS: 108-88-3                        | Dermal     | Non-applicable        | Non-applicable        | 226 mg/kg              | Non-applicable          |
| EC: 203-625-9                        | Inhalation | 226 mg/m <sup>3</sup> | 226 mg/m <sup>3</sup> | 56,5 mg/m <sup>3</sup> | 56,5 mg/m <sup>3</sup>  |
| Xylene                               | Oral       | Non-applicable        | Non-applicable        | 1,6 mg/kg              | Non-applicable          |
| CAS: 1330-20-7                       | Dermal     | Non-applicable        | Non-applicable        | 108 mg/kg              | Non-applicable          |
| EC: 215-535-7                        | Inhalation | Non-applicable        | Non-applicable        | 14,8 mg/m <sup>3</sup> | Non-applicable          |
| 2-methoxy-1-methylethyl acetate      | Oral       | Non-applicable        | Non-applicable        | 1,67 mg/kg             | Non-applicable          |
| CAS: 108-65-6                        | Dermal     | Non-applicable        | Non-applicable        | 54,8 mg/kg             | Non-applicable          |
| EC: 203-603-9                        | Inhalation | Non-applicable        | Non-applicable        | 33 mg/m <sup>3</sup>   | Non-applicable          |
| Cobalt bis(2-ethylhexanoate)         | Oral       | Non-applicable        | Non-applicable        | 0,0558 mg/kg           | Non-applicable          |
| CAS: 136-52-7                        | Dermal     | Non-applicable        | Non-applicable        | Non-applicable         | Non-applicable          |
| EC: 205-250-6                        | Inhalation | Non-applicable        | Non-applicable        | Non-applicable         | 0,037 mg/m <sup>3</sup> |
| 2-butanone oxime                     | Oral       | Non-applicable        | Non-applicable        | Non-applicable         | Non-applicable          |
| CAS: 96-29-7                         | Dermal     | 1,5 mg/kg             | Non-applicable        | 0,78 mg/kg             | Non-applicable          |
| EC: 202-496-6                        | Inhalation | Non-applicable        | Non-applicable        | 2,7 mg/m <sup>3</sup>  | 2 mg/m <sup>3</sup>     |
| 2-ethylhexanoic acid, zirconium salt | Oral       | Non-applicable        | Non-applicable        | 7,9 mg/kg              | Non-applicable          |
| CAS: 22464-99-9                      | Dermal     | Non-applicable        | Non-applicable        | 7,9 mg/kg              | Non-applicable          |
| EC: 245-018-1                        | Inhalation | Non-applicable        | Non-applicable        | 2,5 mg/m <sup>3</sup>  | Non-applicable          |

PNEC:

| Identification                  |              |                |                         |              |
|---------------------------------|--------------|----------------|-------------------------|--------------|
| Toluene                         | STP          | 13,61 mg/L     | Fresh water             | 0,68 mg/L    |
| CAS: 108-88-3                   | Soil         | 2,89 mg/kg     | Marine water            | 0,68 mg/L    |
| EC: 203-625-9                   | Intermittent | 0,68 mg/L      | Sediment (Fresh water)  | 16,39 mg/kg  |
|                                 | Oral         | Non-applicable | Sediment (Marine water) | 16,39 mg/kg  |
| Xylene                          | STP          | 6,58 mg/L      | Fresh water             | 0,327 mg/L   |
| CAS: 1330-20-7                  | Soil         | 2,31 mg/kg     | Marine water            | 0,327 mg/L   |
| EC: 215-535-7                   | Intermittent | 0,327 mg/L     | Sediment (Fresh water)  | 12,46 mg/kg  |
|                                 | Oral         | Non-applicable | Sediment (Marine water) | 12,46 mg/kg  |
| 2-methoxy-1-methylethyl acetate | STP          | 100 mg/L       | Fresh water             | 0,635 mg/L   |
| CAS: 108-65-6                   | Soil         | 0,29 mg/kg     | Marine water            | 0,0635 mg/L  |
| EC: 203-603-9                   | Intermittent | 6,35 mg/L      | Sediment (Fresh water)  | 3,29 mg/kg   |
|                                 | Oral         | Non-applicable | Sediment (Marine water) | 0,329 mg/kg  |
| Cobalt bis(2-ethylhexanoate)    | STP          | 0,37 mg/L      | Fresh water             | 0,00051 mg/L |
| CAS: 136-52-7                   | Soil         | 7,9 mg/kg      | Marine water            | 0,00236 mg/L |
| EC: 205-250-6                   | Intermittent | Non-applicable | Sediment (Fresh water)  | 9,5 mg/kg    |
|                                 | Oral         | Non-applicable | Sediment (Marine water) | 9,5 mg/kg    |



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Identification                       |              |                |                         |                |
|--------------------------------------|--------------|----------------|-------------------------|----------------|
| 2-butanone oxime                     | STP          | 177 mg/L       | Fresh water             | 0,256 mg/L     |
| CAS: 96-29-7                         | Soil         | Non-applicable | Marine water            | Non-applicable |
| EC: 202-496-6                        | Intermittent | 0,118 mg/L     | Sediment (Fresh water)  | Non-applicable |
|                                      | Oral         | Non-applicable | Sediment (Marine water) | Non-applicable |
| 2-ethylhexanoic acid, zirconium salt | STP          | 71,7 mg/L      | Fresh water             | 0,36 mg/L      |
| CAS: 22464-99-9                      | Soil         | 1,06 mg/kg     | Marine water            | 0,036 mg/L     |
| EC: 245-018-1                        | Intermittent | 0,493 mg/L     | Sediment (Fresh water)  | 6,37 mg/kg     |
|                                      | Oral         | Non-applicable | Sediment (Marine water) | 0,637 mg/kg    |

## 8.2 Exposure controls:

A.- General security and hygiene measures in the work place

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

| Pictogram                                    | PPE                               | Labelling | CEN Standard        | Remarks   |
|--|-----------------------------------|-----------|---------------------|---|
| Mandatory<br>respiratory tract<br>protection | Filter mask for gases and vapours |           | EN 405:2001+A1:2009 | Replace when there is a taste or smell of the<br>contaminant inside the face mask. If the<br>contaminant comes with warnings it is<br>recommended to use isolation equipment. |

C.- Specific protection for the hands

| Pictogram                    | PPE  | Labelling | CEN Standard  | Remarks  |
|------------------------------|--|-----------|---|--|
| Mandatory hand<br>protection | NON-disposable chemical<br>protective gloves |           | EN ISO 374-1:2016<br>EN 16523-1:2015<br>EN 420:2003+A1:2009 | The Breakthrough Time indicated by the<br>manufacturer must exceed the period during which<br>the product is being used. Do not use protective<br>creams after the product has come into contact<br>with skin. |

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

| Pictogram                    | PPE         | Labelling | CEN Standard  | Remarks   |
|------------------------------|-------------|-----------|---|---|
| Mandatory face<br>protection | Face shield | CAT II    | EN 166:2001<br>EN 167:2001<br>EN 168:2001<br>EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram                             | PPE  | Labelling | CEN Standard  | Remarks   |
|---------------------------------------|--|-----------|---|---|
| Mandatory complete<br>body protection | Disposable clothing for<br>protection against chemical<br>risks, with antistatic and<br>fireproof properties |           | EN 1149-1,2,3<br>EN 13034:2005+A1:2009<br>EN ISO 13982-<br>1:2004/A1:2010<br>EN ISO 6529:2013<br>EN ISO 6530:2005<br>EN ISO 13688:2013<br>EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
| Mandatory foot<br>protection          | Safety footwear for<br>protection against chemical<br>risk, with antistatic and heat<br>resistant properties |           | EN ISO 13287:2012<br>EN ISO 20345:2011<br>EN 13832-1:2019   | Replace boots at any sign of deterioration.   |



## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## MORAVIA - VENTOSHORT SK10-9002

| SECTION | 8: EXPOSURE CONTR  | OLS/PERSONAL PROTECTION (   | (continued)       |  |  |  |  |
|---------|--|---|-------------------|--|--|--|--|
|         | Emergency measure  | Standards   | Emergency measure | Standards                                      |  |  |  |
|         | Emergency shower   | ANSI Z358-1<br>ISO 3864-1:2011, ISO 3864-4:2011   | Eyewash stations  | DIN 12 899<br>ISO 3864-1:2011, ISO 3864-4:2011 |  |  |  |
| Env     | vironmental exposure c   | ontrols:  | -                 |  |  |  |  |
| Vol     | atile organic compound   | nd its container. For additional inform<br><b>Is:</b><br>/75/EU, this product has the following |                   | )  |  |  |  |
|         | V.O.C. (Supply):   | 38,95 % weight  | <b>y</b>          |  |  |  |  |
|         | V.O.C. density at 20 °C: 447,93 kg/m <sup>3</sup> (447,93 g/L) |   |                   |  |  |  |  |
|         | Average carbon number: 7,05                                    |   |                   |  |  |  |  |
|         | Average molecular weight                                       | 97,22 g/mol   |                   |  |  |  |  |
|         |  |   |                   |  |  |  |  |
| ECTION  | 9: PHYSICAL AND CH   | EMICAL PROPERTIES   |                   |  |  |  |  |
| .1 Inf  | ormation on basic phys   | ical and chemical properties:   |                   |  |  |  |  |
| For     | complete information see                                       | the product datasheet.  |                   |  |  |  |  |
| Ар      | pearance:  |   |                   |  |  |  |  |

| Appearance:                                  |                         |
|--|-------------------------|
| Physical state at 20 °C:                     | Liquid                  |
| Appearance:                                  | Not available           |
| Colour:                                      | Several                 |
| Odour:                                       | Not available           |
| Odour threshold:                             | Non-applicable *        |
| Volatility:                                  |                         |
| Boiling point at atmospheric pressure:       | 116 °C                  |
| Vapour pressure at 20 °C:                    | 2518 Pa                 |
| Vapour pressure at 50 °C:                    | 10588,06 Pa (10,59 kPa) |
| Evaporation rate at 20 °C:                   | Non-applicable *        |
| Product description:                         |                         |
| Density at 20 °C:                            | 1120 - 1180 kg/m³       |
| Relative density at 20 °C:                   | 1,12 - 1,18             |
| Dynamic viscosity at 20 °C:                  | Non-applicable *        |
| Kinematic viscosity at 20 °C:                | Non-applicable *        |
| Kinematic viscosity at 40 °C:                | <20,5 cSt               |
| Concentration:                               | Non-applicable *        |
| pH:  | Non-applicable *        |
| Vapour density at 20 °C:                     | Non-applicable *        |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable *        |
| Solubility in water at 20 °C:                | Non-applicable *        |
| Solubility properties:                       | Non-applicable *        |
| Decomposition temperature:                   | Non-applicable *        |
| Melting point/freezing point:                | Non-applicable *        |
| Explosive properties:                        | Non-applicable *        |
| Oxidising properties:                        | Non-applicable *        |



| CTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued) |   |  |  |  |
|---|---|--|--|--|
| Flammability:   |   |  |  |  |
| Flash Point:  | 10 °C   |  |  |  |
| Flammability (solid, gas):                            | Non-applicable *                                  |  |  |  |
| Autoignition temperature:                             | 315 °C  |  |  |  |
| Lower flammability limit:                             | Not available                                     |  |  |  |
| Upper flammability limit:                             | Not available                                     |  |  |  |
| Explosive:  |   |  |  |  |
| Lower explosive limit:                                | Non-applicable *                                  |  |  |  |
| Upper explosive limit:                                | Non-applicable *                                  |  |  |  |
| .2 Other information:                                 |   |  |  |  |
| Surface tension at 20 °C:                             | Non-applicable *                                  |  |  |  |
| Refraction index:                                     | Non-applicable *                                  |  |  |  |
| *Not relevant due to the nature of the product,       | ot providing information property of its hazards. |  |  |  |

# SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight            | Humidity       |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable     | Not applicable   | Risk of combustion      | Avoid direct impact | Not applicable |

#### **10.5** Incompatible materials:

| Acids              | Water          | Oxidising materials | Combustible materials | Others                        |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable        | Avoid alkalis or strong bases |

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):



## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
  - IARC: Toluene (3); Xylene (3)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Reproductive toxicity: Suspected of damaging the unborn child.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

#### Other information:

Non-applicable

### Specific toxicology information on the substances:

| Identification                       | A               | Acute toxicity       |     |
|--------------------------------------|-----------------|----------------------|-----|
| Toluene                              | LD50 oral       | 5580 mg/kg           | Rat |
| CAS: 108-88-3                        | LD50 dermal     | 12124 mg/kg          | Rat |
| EC: 203-625-9                        | LC50 inhalation | 28,1 mg/L (4 h)      | Rat |
| Xylene                               | LD50 oral       | 2100 mg/kg           | Rat |
| CAS: 1330-20-7                       | LD50 dermal     | 1100 mg/kg (ATEi)    | Rat |
| EC: 215-535-7                        | LC50 inhalation | 11 mg/L (4 h) (ATEi) |     |
| 2-methoxy-1-methylethyl acetate      | LD50 oral       | 8532 mg/kg           | Rat |
| CAS: 108-65-6                        | LD50 dermal     | 5100 mg/kg           | Rat |
| EC: 203-603-9                        | LC50 inhalation | 30 mg/L (4 h)        | Rat |
| 2-butanone oxime                     | LD50 oral       | 2100 mg/kg           | Rat |
| CAS: 96-29-7                         | LD50 dermal     | 1100 mg/kg           | Rat |
| EC: 202-496-6                        | LC50 inhalation | Non-applicable       |     |
| 2-ethylhexanoic acid, zirconium salt | LD50 oral       | 2043 mg/kg           | Rat |
| CAS: 22464-99-9                      | LD50 dermal     | Non-applicable       |     |
| EC: 245-018-1                        | LC50 inhalation | Non-applicable       |     |

## SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Revised: 09/06/2020



# SECTION 12: ECOLOGICAL INFORMATION (continued)

## 12.1 Toxicity:

| Identification                            |      | Acute toxicity       | Species                 | Genus     |
|---|------|----------------------|-------------------------|-----------|
| Toluene                                   | LC50 | 13 mg/L (96 h)       | Carassius auratus       | Fish      |
| CAS: 108-88-3                             | EC50 | 11.5 mg/L (48 h)     | Daphnia magna           | Crustacea |
| EC: 203-625-9                             | EC50 | 125 mg/L (48 h)      | Scenedesmus subspicatus | Algae     |
| Xylene                                    | LC50 | 13.5 mg/L (96 h)     | Oncorhynchus mykiss     | Fish      |
| CAS: 1330-20-7                            | EC50 | 3.4 mg/L (48 h)      | Ceriodaphnia dubia      | Crustacea |
| EC: 215-535-7                             | EC50 | 10 mg/L (72 h)       | Skeletonema costatum    | Algae     |
| Hydrocarbons, C9-unsaturated, polymerised | LC50 | 10 - 100 mg/L (96 h) |                         | Fish      |
| CAS: 71302-83-5                           | EC50 | 10 - 100 mg/L        |                         | Crustacea |
| EC: 615-276-3                             | EC50 | 10 - 100 mg/L        |                         | Algae     |
| 2-methoxy-1-methylethyl acetate           | LC50 | 161 mg/L (96 h)      | Pimephales promelas     | Fish      |
| CAS: 108-65-6                             | EC50 | 481 mg/L (48 h)      | Daphnia sp.             | Crustacea |
| EC: 203-603-9                             | EC50 | Non-applicable       |                         |           |
| Cobalt bis(2-ethylhexanoate)              | LC50 | 0.1 - 1 mg/L (96 h)  |                         | Fish      |
| CAS: 136-52-7                             | EC50 | 0.1 - 1 mg/L         |                         | Crustacea |
| EC: 205-250-6                             | EC50 | 0.1 - 1 mg/L         |                         | Algae     |
| 2-butanone oxime                          | LC50 | 843 mg/L (96 h)      | Pimephales promelas     | Fish      |
| CAS: 96-29-7                              | EC50 | 750 mg/L (48 h)      | Daphnia magna           | Crustacea |
| EC: 202-496-6                             | EC50 | 83 mg/L (72 h)       | Scenedesmus subspicatus | Algae     |
| 2-ethylhexanoic acid, zirconium salt      | LC50 | 270 mg/L (96 h)      | N/A                     | Fish      |
| CAS: 22464-99-9                           | EC50 | Non-applicable       |                         |           |
| EC: 245-018-1                             | EC50 | Non-applicable       |                         |           |

## 12.2 Persistence and degradability:

| Identification                       | De       | gradability    | Biode           | egradability   |
|--------------------------------------|----------|----------------|-----------------|----------------|
| Toluene                              | BOD5     | 2.5 g O2/g     | Concentration   | 100 mg/L       |
| CAS: 108-88-3                        | COD      | Non-applicable | Period          | 14 days        |
| EC: 203-625-9                        | BOD5/COD | Non-applicable | % Biodegradable | 100 %          |
| Xylene                               | BOD5     | Non-applicable | Concentration   | Non-applicable |
| CAS: 1330-20-7                       | COD      | Non-applicable | Period          | 28 days        |
| EC: 215-535-7                        | BOD5/COD | Non-applicable | % Biodegradable | 88 %           |
| 2-methoxy-1-methylethyl acetate      | BOD5     | Non-applicable | Concentration   | 785 mg/L       |
| CAS: 108-65-6                        | COD      | Non-applicable | Period          | 8 days         |
| EC: 203-603-9                        | BOD5/COD | Non-applicable | % Biodegradable | 100 %          |
| 2-butanone oxime                     | BOD5     | Non-applicable | Concentration   | 100 mg/L       |
| CAS: 96-29-7                         | COD      | Non-applicable | Period          | 28 days        |
| EC: 202-496-6                        | BOD5/COD | Non-applicable | % Biodegradable | 24 %           |
| 2-ethylhexanoic acid, zirconium salt | BOD5     | Non-applicable | Concentration   | 20 mg/L        |
| CAS: 22464-99-9                      | COD      | Non-applicable | Period          | 28 days        |
| EC: 245-018-1                        | BOD5/COD | Non-applicable | % Biodegradable | 99 %           |

## 12.3 Bioaccumulative potential:

| Identification                  |           | Bioaccumulation potential |  |  |
|---------------------------------|-----------|---------------------------|--|--|
| Toluene                         | BCF       | 13                        |  |  |
| CAS: 108-88-3                   | Pow Log   | 2.73                      |  |  |
| EC: 203-625-9                   | Potential | Low                       |  |  |
| Xylene                          | BCF       | 9                         |  |  |
| CAS: 1330-20-7                  | Pow Log   | 2.77                      |  |  |
| EC: 215-535-7                   | Potential | Low                       |  |  |
| 2-methoxy-1-methylethyl acetate | BCF       | 1                         |  |  |
| CAS: 108-65-6                   | Pow Log   | 0.43                      |  |  |
| EC: 203-603-9                   | Potential | Low                       |  |  |
| 2-butanone oxime                | BCF       | 5                         |  |  |
| CAS: 96-29-7                    | Pow Log   | 0.59                      |  |  |
| EC: 202-496-6                   | Potential | Low                       |  |  |



## SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification                       | Bioaccumulation potential |      |
|--------------------------------------|---------------------------|------|
| 2-ethylhexanoic acid, zirconium salt | BCF                       |      |
| CAS: 22464-99-9                      | Pow Log                   | 2.96 |
| EC: 245-018-1                        | Potential                 |      |

### 12.4 Mobility in soil:

| Identification                       | Absorp          | tion/desorption      | Volat      | tility                         |  |
|--------------------------------------|-----------------|----------------------|------------|--------------------------------|--|
| Toluene                              | Кос             | 178                  | Henry      | 672,8 Pa·m³/mol                |  |
| CAS: 108-88-3                        | Conclusion      | Moderate             | Dry soil   | Yes                            |  |
| EC: 203-625-9                        | Surface tension | 2,793E-2 N/m (25 °C) | Moist soil | Yes                            |  |
| Xylene                               | Кос             | 202                  | Henry      | 524,86 Pa·m <sup>3</sup> /mol  |  |
| CAS: 1330-20-7                       | Conclusion      | Moderate             | Dry soil   | Yes                            |  |
| EC: 215-535-7                        | Surface tension | Non-applicable       | Moist soil | Yes                            |  |
| 2-butanone oxime                     | Кос             | 3                    | Henry      | Non-applicable                 |  |
| CAS: 96-29-7                         | Conclusion      | Very High            | Dry soil   | Non-applicable                 |  |
| EC: 202-496-6                        | Surface tension | 2,57E-2 N/m (25 °C)  | Moist soil | Non-applicable                 |  |
| 2-ethylhexanoic acid, zirconium salt | Кос             | Non-applicable       | Henry      | 2,94E-1 Pa·m <sup>3</sup> /mol |  |
| CAS: 22464-99-9                      | Conclusion      | Non-applicable       | Dry soil   | Yes                            |  |
| EC: 245-018-1                        | Surface tension | Non-applicable       | Moist soil | Yes                            |  |

## 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

### 12.6 Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

#### **13.1** Waste treatment methods:

| Code      | Description   | Waste class (Regulation (EU) No<br>1357/2014) |
|-----------|---|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances | Dangerous                                     |

### Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

#### **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

## SECTION 14: TRANSPORT INFORMATION

## Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:



| SECTION 14: TRANSPORT   | INFORMATION (continued)   |                     |  |  |
|-------------------------|---|---------------------|--|--|
| 14.1                    | UN number:  | UN1263              |  |  |
|                         | UN proper shipping name:  | PAINT               |  |  |
|                         | Transport hazard class(es):   | 3                   |  |  |
|                         | Labels:   | 3                   |  |  |
| 14.4                    | Packing group:  | II                  |  |  |
| 3 14.5                  | Environmental hazards:  | No                  |  |  |
| 14.6                    | Special precautions for user  |                     |  |  |
|                         | Special regulations:  | 163, 367, 640D, 650 |  |  |
|                         | Tunnel restriction code:  | D/E                 |  |  |
|                         | Physico-Chemical properties:  | see section 9       |  |  |
|                         | Limited quantities:   | 5 L                 |  |  |
| 14.7                    | Transport in bulk according<br>to Annex II of Marpol and<br>the IBC Code: | Non-applicable      |  |  |
| Transport of dangero    |   |                     |  |  |
|                         | With regard to IMDG 39-18:  |                     |  |  |
| 14.1                    | UN number:  | UN1263              |  |  |
|                         | UN proper shipping name:  | PAINT               |  |  |
|                         | Transport hazard class(es):   | 3                   |  |  |
|                         | Labels:   | 3                   |  |  |
| 14.4                    | Packing group:  | II                  |  |  |
| 3 14.5                  | Environmental hazards:  | No                  |  |  |
| 14.6                    | Special precautions for user  |                     |  |  |
|                         | Special regulations:  | 367, 163            |  |  |
|                         | EmS Codes:  | F-E, S-E            |  |  |
|                         | Physico-Chemical properties:  | see section 9       |  |  |
|                         | Limited quantities:   | 5 L                 |  |  |
|                         | Segregation group:  | Non-applicable      |  |  |
| 14.7                    | Transport in bulk according<br>to Annex II of Marpol and<br>the IBC Code: | Non-applicable      |  |  |
| Transport of dangero    |   |                     |  |  |
| With regard to IATA/ICA | AO 2020:  |                     |  |  |
| 14.1                    | UN number:  | UN1263              |  |  |
| 14.2                    | UN proper shipping name:  | PAINT               |  |  |
| 14.3                    | Transport hazard class(es):   | 3                   |  |  |
|                         | Labels:   | 3                   |  |  |
| <b>•</b>                | Packing group:  | II                  |  |  |
|                         | Environmental hazards:  | No                  |  |  |
| 14.6                    | Special precautions for user  |                     |  |  |
| 447                     | Physico-Chemical properties:  | see section 9       |  |  |
| 14.7                    | Transport in bulk according<br>to Annex II of Marpol and<br>the IBC Code: | Non-applicable      |  |  |

# SECTION 15: REGULATORY INFORMATION

| 15.1 | Safety, health and environmental regulations/legislation specific for the substance or mixture:                  |
|------|--|
|      | Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable            |
|      | Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable                 |
|      | Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable                      |
|      | Article 95, REGULATION (EU) No 528/2012: Non-applicable  |
|      | REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable |
|      | Seveso III:  |
|      | - CONTINUED ON NEXT BAGE -   |



#### SECTION 15: REGULATORY INFORMATION (continued) Lower-tier Upper-tier Section Description requirements requirements P5c 5000 50000 Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....): Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: - metallic glitter intended mainly for decoration, artificial snow and frost, - "whoopee" cushions, - silly string aerosols, imitation excrement, horns for parties, - decorative flakes and foams, artificial cobwebs. stink bombs. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: 'For professional users only'. Shall not be used in: and ashtrays, -tricks and jokes, -games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

## Other legislation:

The product could be affected by sectorial legislation

### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

## SECTION 16: OTHER INFORMATION

### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16): • Supplementary information

### Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation

H336: May cause drowsiness or dizziness

H373: May cause damage to organs through prolonged or repeated exposure

H361d: Suspected of damaging the unborn child.

H317: May cause an allergic skin reaction

H304: May be fatal if swallowed and enters airways

H225: Highly flammable liquid and vapour

### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### CLP Regulation (EC) No 1272/2008:



| SECTION 16: OTHER INFORMATION (continued)  |
|--|
| Acute Tox. 4: H312 - Harmful in contact with skin<br>Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled  |
| Aquatic Acute 1: H400 - Very toxic to aquatic life<br>Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects<br>Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways  |
| Carc. 2: H351 - Suspected of causing cancer<br>Eye Dam. 1: H318 - Causes serious eye damage  |
| Eye Irrit. 2: H319 - Causes serious eye irritation<br>Flam. Liq. 2: H225 - Highly flammable liquid and vapour<br>Flam. Liq. 3: H226 - Flammable liquid and vapour  |
| Repr. 1B: H360 - May damage fertility or the unborn child<br>Repr. 2: H361d - Suspected of damaging the unborn child.  |
| Skin Irrit. 2: H315 - Causes skin irritation<br>Skin Sens. 1: H317 - May cause an allergic skin reaction   |
| Skin Sens. 1A: H317 - May cause an allergic skin reaction<br>STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure<br>STOT SE 3: H336 - May cause drowsiness or dizziness  |
| Classification procedure:  |
| Skin Irrit. 2: Calculation method<br>STOT SE 3: Calculation method<br>STOT RE 2: Calculation method<br>Repr. 2: Calculation method<br>Skin Sens. 1A: Calculation method<br>Asp. Tox. 1: Calculation method<br>Flam. Liq. 2: Calculation method (2.6.4.3) |
| Advice related to training:  |
| Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.                               |
| Principal bibliographical sources:   |
| http://echa.europa.eu<br>http://eur-lex.europa.eu  |
| Abbreviations and acronyms:  |
| ADR: European agreement concerning the international carriage of dangerous goods by road<br>IMDG: International maritime dangerous goods code<br>IATA: International Air Transport Association   |
| ICAO: International Civil Aviation Organisation<br>COD: Chemical Oxygen Demand<br>BOD5: 5-day biochemical oxygen demand  |
| BCF: Bioconcentration factor<br>LD50: Lethal Dose 50   |
| LC50: Lethal Concentration 50<br>EC50: Effective concentration 50<br>Log-POW: Octanol-water partition coefficient  |
| Koc: Partition coefficient of organic carbon   |
|  |

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.